


## ProLine + Touchscreen

### The next generation

The next generation of Ultra HD touchscreens with outstanding image and sound quality. With ProWrite Ink writing will feel as fluent as a writing with pen on paper. Of course great software is included. Central, Reflect, ProNote and Presenter will help you teach, share and collaborate at the highest level.



### Specifications

<b>Screen</b>	65"	75"
Bezel color	Brushed aluminium (grey)	Brushed aluminium (grey)
Diagonal	65 inch	75 inch
Panel type	Ultra HD LED	Ultra HD LED
Resolution	3840 x 2160 @ 60Hz	3840 x 2160 @ 60Hz
Glass plate	Anti-Glare	Anti-Glare
Glass Thickness	4 mm / 0.16 inches	4 mm / 0.16 inches
Glass Hardness	Mhos 7	Mhos 7
Aspect ratio	16:9	16:9
Contrast ratio	1200:1	1200:1
Brightness	450cd/m2	410cd/m2
Number of colors	10 bit (1.07B)	10 bit (1.07B)
Viewing Angle	178°	178°
Panel Refresh Rate	60hz	60hz
<b>Modules</b>	65"	75"
PC module slot	Yes, OPS	Yes, OPS
<b>Touch Type</b>	65"	75"
Type	IR-pro	IR-pro
Multi-touch	Yes (20 points)	Yes (20 points)
Multi writing	Yes (10 points)	Yes (10 points)
Auto-calibration	Yes	Yes
Resistant to sunlight	Yes	Yes
Supported OS	Windows 7, 8.1 & 10/Mac OS/Linux/Android and Chrome OS	Windows 7, 8.1 & 10/Mac OS/Linux/Android and Chrome OS

<b>Audio</b>	65"	75"
Speakers	3-Way speaker	3-Way speaker
Power	2 x 14W/ 8Ω	2 x 14W/ 8Ω
Microphone	Yes, Wide-area	Yes, Wide-area
<b>Prowrite pen technology</b>	65"	75"
Active Pen	Yes	Yes
Pressure sensitivity	2048 levels	2048 levels
Connectivity	EMR + AES	EMR + AES
Power	Charging station (Automatic charging)	Charging station (Automatic charging)
Hoover function	Yes	Yes
Angle recognition	No	No
Palm rejection	Yes	Yes
Pairing	No, plug & play	No, plug & play
Windows ink support	Yes	Yes
<b>Special features</b>	65"	75"
Prowise Central	Yes	Yes
NFC reader/writer	Yes	Yes
Pen Charging station	Yes	Yes
Over the Air Updates (OTA)	Yes	Yes
<b>Connections</b>	65"	75"
HDMI 2.0	2	2
HDMI 2.0 (CEC and ARC)	1 (With CEC and ARC support)	1 (With CEC and ARC support)
Display Port 1.2	1	1
Audio output analog	3,5 mm Stereo Jack (adjustable)	3,5 mm Stereo Jack (adjustable)
Audio output digital	Coaxial (fixed)	Coaxial (fixed)
RS232 control	1 (Sub-D, 9 pins)	1 (Sub-D, 9 pins)
AV in	No	No
USB Touch port	1 (USB-B female)	1 (USB-B female)
USB 2.0	1	1
USB 3.0	2	2
Webcam Mount + top USB	Yes	Yes
Wi-Fi for online updates	Yes	Yes
<b>General Information</b>	65"	75"
Voltage	~ 100-240 V (50/60Hz)	~ 100-240 V (50/60Hz)
Power consumption (Without modules)	TBD	TBD
Stand-by power consumption	≤ 0,5 Watt	≤ 0,5 Watt
Gross Weight	TBD	TBD
Netto Weight	69 kg 152.1 lbs	88 kg, 194 lbs
Dimensions of the screen (W x H x D)	1533.8 x 973.8 x 94.8 mm / 60.4 x 38.3 x 3.7 inches	1765.3 x 1108.4 x 94.8 mm / 69.5 x 43.6 x 3.7 inches
Dimensions of the total packing (W x H x D)	TBD	TBD
VESA Standard	VESA 800 x 600 mm	VESA 800 x 600 mm
Certifications	CE-EMC/FCC/IC/ROHS/UL+CB and RCM	CE-EMC/FCC/IC/ROHS/UL+CB and RCM
Warranty	5 years	5 years

**Environmental conditions** 65"

Operation Temperature	0°C - 38°C / 32 - 100.4°F
Storage Temperature	-20°C - 60°C / -4 - 140°F
Storage Humidity	10% - 90%
Operation Humidity	10% - 90%

## 75"

Operation Temperature	0°C - 38°C / 32 - 100.4°F
Storage Temperature	-20°C - 60°C / -4 - 140°F
Storage Humidity	10% - 90%
Operation Humidity	10% - 90%